



PCA-1269

INSTRUCTIONS

Support d'ancrage de treuil
pour arbres avec courroie



Utiliser le système d'ancrage pour arbres avec courroie:

- 1- Installez la courroie dans l'ancrage de gauche en s'assurant de placer le crochet vers l'avant (photo #1);
- 2- Placez le système d'ancrage à la base de l'arbre et passez la courroie dans le système à rochet de droite (photo #2);
- 3- Glissez le système d'ancrage vers le haut jusqu'à la hauteur désirée (photo #3);
- 4- Serrez la courroie à l'aide de la poignée à cliquets en s'assurant que le système d'ancrage soit bien appuyé sur l'arbre (photo #4);
- 5- Accrochez les crochets de sûreté du treuil aux ouvertures rectangulaires du système d'ancrage (photo #5);
- 6- Enroulez la corde autour du tambour et tirez. Le treuil s'alignera automatiquement avec la charge (photo #6);

⚠ ATTENTION

APRÈS AVOIR MIS LE DISPOSITIF EN CHARGE, RELÂCHEZ LA TENSION DU TREUIL.
VÉRIFIEZ LA SOLIDITÉ DE L'ANCRAGE ET RESSERREZ LA COURROIE.

⚠ PRECAUTION

SI VOUS DEVEZ TIRER VERS LE BAS, VOUS DEVEZ INSTALLER UNE POULIE OU
UN ROULEAU AFIN D'ÉVITER D'ENDOMMAGER LA PLAQUE D'APPUI.





PCA-1269

INSTRUCTIONS

Tree mount winch anchor
with strap



Using the tree mount winch anchor:

- 1- Install the strap hook into the anchor point on the left while making sure the hook's opening is in front (picture #1);
- 2- Place the tree mount winch anchor at the base of the tree and feed the strap's end through the ratchet system on the right (picture #2);
- 3- Slide the whole set-up upward to the desired height (picture #3);
- 4- Tighten the strap with the ratchet handle while making sure the winch anchor offers maximum contact surface with the tree (picture #4);
- 5- Attach the winch anchor hooks to the winch anchor rectangular holes (picture #5);
- 6- Wrap the rope around the drum and start winching. The winch will align itself automatically with the load (picture #6);

⚠ WARNING

AFTER PULLING FOR A FEW SECONDS WITH THE TREE MOUNT, RELEASE THE TENSION OFF THE WINCH. CHECK THE SOLIDITY OF THE INSTALLATION AND TIGHTEN THE SLING AGAIN.

⚠ CAUTION

IF YOU NEED TO PULL DOWNWARD, YOU WILL NEED TO INSTALL EITHER A PULLEY OR A ROLLER TO PREVENT DAMAGE TO THE WINCH SUPPORT PLATE.

